




Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power $\Delta T=50K$ (75/65/20 °C) [W]	Power $\Delta T=46K$ (75/65/24 °C) [W]	Power $\Delta T=30K$ (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B	A							
AT003500688014010000	350	688	157	300	50	300	0,51	5,6	2,7	286	259	155	-
AT003500864014010000	350	864	157	300	50	300	0,63	6,9	3,4	358	324	194	300
AT003501040014010000	350	1040	157	300	50	300	0,76	8,1	4,1	430	389	233	300
AT003501216014010000	350	1216	157	300	50	300	0,89	9,4	4,8	501	453	272	300
AT003501392014010000	350	1392	157	300	50	300	1,01	10,7	5,5	573	518	310	300
AT003501568014010000	350	1568	157	300	50	300	1,14	11,9	6,2	644	582	347	600
AT004500688014010000	450	688	157	400	50	400	0,59	6,3	3,1	333	301	181	300
AT004500864014010000	450	864	157	400	50	400	0,74	7,8	3,9	417	377	226	300
AT004501040014010000	450	1040	157	400	50	400	0,89	9,3	4,6	500	452	271	300
AT004501216014010000	450	1216	157	400	50	400	1,03	10,7	5,4	583	528	316	300
AT004501392014010000	450	1392	157	400	50	400	1,18	12,2	6,2	666	602	360	600
AT004501568014010000	450	1568	157	400	50	400	1,33	13,6	7,0	750	678	404	600
AT005500688014010000	550	688	157	500	50	500	0,68	7,2	3,5	380	344	206	300
AT005500864014010000	550	864	157	500	50	500	0,85	8,9	4,4	475	430	257	300
AT005501040014010000	550	1040	157	500	50	500	1,03	10,6	5,3	570	516	309	300
AT005501216014010000	550	1216	157	500	50	500	1,20	12,2	6,1	665	602	360	600
AT005501392014010000	550	1392	157	500	50	500	1,37	13,9	7,0	760	687	411	600
AT005501568014010000	550	1568	157	500	50	500	1,54	15,6	7,9	855	773	461	600
AT006500688014010000	650	688	157	600	50	600	0,76	7,8	3,8	427	386	232	300
AT006500864014010000	650	864	157	600	50	600	0,95	9,7	4,8	534	483	289	300
AT006501040014010000	650	1040	157	600	50	600	1,13	11,5	5,7	640	579	347	600
AT006501216014010000	650	1216	157	600	50	600	1,32	13,4	6,7	747	676	405	600
AT006501392014010000	650	1392	157	600	50	600	1,51	15,2	7,7	854	772	461	600
AT006501568014010000	650	1568	157	600	50	600	1,70	17,0	8,6	960	868	517	900



Finishing and warranty:	Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;	
Mounting brackets:	brackets in the same colour as the radiator are included	
Valve:	order separately	
Heater :	order separately	
Working pressure:	10 bars	
Maximum temperature:	120 °C	
Connections:		<ul style="list-style-type: none"> - inner threads G 1/2 - air-vent plug G 1/2, screwed in the upper hole of the collector is included
Remarks:	If the radiator is in a different colour than white, the type and depth of the bracket are different than in the table.	

