

| Type                 | Width [mm] | Height [mm] | Depth from wall [mm] | Connections spacing [mm] | Connections distance from the wall [mm] | Brackets spacing [mm] | Heating surface [m <sup>2</sup> ] | Weight [kg] | Capacity [dm <sup>3</sup> ] | Power ΔT=50K (75/65/20 °C) [W] | Power ΔT=46K (75/65/24 °C) [W] | Power ΔT=30K (55/45/20 °C) [W] | Electric heater maximum power [W] |
|----------------------|------------|-------------|----------------------|--------------------------|---|-----------------------|-----------------------------------|-------------|-----------------------------|--------------------------------|--------------------------------|--------------------------------|-----------------------------------|
|                      | W          | H           | D                    | C                        | B                                       |                       |                                   |             |                             |                                |                                |                                |                                   |
| B00055509041400D0000 | 555        | 904         | 65-70                | 50                       | 50-55                                   | 515                   | 0,51                              | 6,2         | 3,1                         | 292                            | 264                            | 158                            | 300                               |
| B00055511201400D0000 | 555        | 1120        | 65-70                | 50                       | 50-55                                   | 515                   | 0,62                              | 7,3         | 3,7                         | 352                            | 319                            | 190                            | 300                               |
| B00055513361400D0000 | 555        | 1336        | 65-70                | 50                       | 50-55                                   | 515                   | 0,72                              | 8,5         | 4,2                         | 411                            | 372                            | 222                            | 300                               |

Horizontal profiles:

Circuital profile:

|                         |  |  |
|-------------------------|--|--|
| Finishing and warranty: | Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty; |  |
| Mounting brackets:      | brackets in the colour of the radiator are included                        |  |
| Valve:                  | order separately   |  |
| Heater :                | order separately   |  |
| Working pressure:       | 8 bars   |  |
| Maximum temperature:    | 120 °C   |  |
| Connections:            | <br>on request   |  |
|                         | – inner threads G 1/2<br>– air-vent plug G1/8 hidden behind                |  |

