



Kod produktu	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B	A							
FB00595077601G010000	595	776	106-111	50	53-58	525	0,74	10,1	4,2	440	396	232	300
FB00595115401G010000	595	1154	106-111	50	53-58	525	1,14	14,6	6,4	669	603	353	600
FB00595174201G010000	595	1742	106-111	50	53-58	525	1,77	21,7	10,0	1031	927	539	900
FB00746077601G010000	746	776	120-125	50	53-58	676	0,87	11,4	4,8	526	473	276	300
FB00746115401G010000	746	1154	120-125	50	53-58	676	1,35	16,5	7,4	797	716	414	600
FB00746174201G010000	746	1742	120-125	50	53-58	676	2,12	24,8	11,5	1249	1122	647	600



Finishing and warranty:	Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;
Mounting brackets:	brackets in the colour of the radiator are included
Valve:	– integrated, hidden under cover – thermostatic valve included
Heater :	order separately
Accessories:	order separately
Working pressure:	4 bars
Maximum temperature:	120 °C
Connections:	 <ul style="list-style-type: none"> – inner threads G 1/2 – air-vent plug G1/8 positioned behind the radiator
Remarks:	Water inlet on the left side Chrome-plated thermostatic head Radiators painted in other colors than white, have different type and depth of the mounting bracket.

