



Typ	Breite [mm]	Höhe [mm]	Tiefe [mm]	Anschlussabstand [mm]	Abstand der Verschraubung von der Wand [mm]	Halterabstand [mm]	Heizfläche [m ²]	Gewicht [kg]	Wasserinhalt [dm ³]	Leistung ΔT=50K (75/65/20 °C) [W]	Leistung ΔT=46K (75/65/24 °C) [W]	Leistung ΔT=30K (55/45/20 °C) [W]	Max. Leistung vom Elektro-Heizstab [W]
	W	H	D	C	B	A							
FR00608123802B0E0000	608	1238	90-95	50	75-80	568	1,06	10,0	6,6	545	488	278	300
FR00608166702B0E0000	608	1667	90-95	50	75-80	568	1,39	12,9	8,5	712	638	363	600

Waagerechte Rohren



Umfangs Profil:



Fertigstellung und Garantie:

Nanokeramik (Zirkoniumoxid-Beschichtung); + Polyester-Epoxydlack; Garantie 5 Jahre

Befestigungen:

Befestigungsset; Befestigungsset in Heizkörperfarbe

Ventil:

Extra bestellen

Heizstab:

Extra bestellen

Arbeitsdruck:

10 Bar

Max Temperatur:

120 °C

Anschlüsse:



Innengewinde G1/2
Entlüfter G 1/8 versteckt hinten

