




Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m <sup>2</sup> ]	Weight [kg]	Capacity [dm <sup>3</sup> ]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B								
FR00608123802B0E0000	608	1238	90-95	50	75-80	568	1,06	10,0	6,6	545	488	278	300
FR00608166702B0E0000	608	1667	90-95	50	75-80	568	1,39	12,9	8,5	712	638	363	600

Horizontal profiles: 

Circuital profile: 

Finishing and warranty:	Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;
Mounting brackets:	brackets in the colour of the radiator are included
Valve:	order separately
Heater :	order separately
Working pressure:	10 bars
Maximum temperature:	120 °C
Connections:	 <ul style="list-style-type: none"> <li>- inner threads G 1/2</li> <li>- air-vent plug G1/8 hidden behind</li> </ul>

