


Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m <sup>2</sup> ]	Weight [kg]	Capacity [dm <sup>3</sup> ]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B	A							
ML00340160014N071000	340	1600	88	50	53	1504	1,60	19,0	13,2	720	645	369	600
ML00340180014N071000	340	1800	88	50	53	1704	1,80	21,2	14,9	806	722	413	600
ML00340200014N071000	340	2000	88	50	53	1904	2,00	23,4	16,5	892	800	457	600

Lighting

Power LED	Beam Angle	Color Warm White	Voltage	Lifespan
3 x 1,1W	15°	3000K	230V	70000 h



Horizontal manifolds (atypical)  
1,5 mm thick

Finishing and warranty:	Electrophoresis + polyester-epoxy lacquer; 5 year warranty;
Mounting brackets:	set for assembly on the wall; steel box brackets – the same colour as the radiator
Valve:	order separately
Heater:	order separately
Working pressure:	6 bars
Maximum temperature:	120 °C
Connections:	inner threads G 1/2 included and air-vent plug G 1/2 screwed in the upper hole of the collector,
Accessories:	order separately

