



Typ	Breite [mm]	Höhe [mm]	Tiefe [mm]	Anschlussabstand [mm]	Abstand der Verschraubung von der Wand [mm]	Halteabstand [mm]	Heizfläche [m ²]	Gewicht [kg]	Wasserinhalt [dm ³]	Leistung fIT=50K (75/65/20 °C) [W]	Leistung fIT=46K (75/65/24 °C) [W]	Leistung fIT=30K (55/45/20 °C) [W]	Max. Leistung vom Elektro-Heizstab [W]
	W	H	D	C	B	A							
MG00340160014N071000	340	1600	88	50	53	1504	1,60	19,0	13,2	720	645	369	600
MG00340180014N071000	340	1800	88	50	53	1704	1,80	21,2	14,9	806	722	413	600
MG00340200014N071000	340	2000	88	50	53	1904	2,00	23,4	16,5	800	800	457	600

Vertikale Rohren:



Waagerechte Sammelrohren:
Wanddicke 2,5mm



Fertigstellung und Garantie:	Kataphorese + Polyester-Epoxydlack; Garantie 5 Jahre	
Befestigungen:	Befestigungsset; Stahlbefestigungen in Heizkörperfarbe	
Ventil:	Extra bestellen	
Heizstab:	-	
Arbeitsdruck:	6 Bar	
Max Temperatur:	120 °C	
Anschlüsse:		Innengewinde G1/2 Komplett mit Entlüfter G1/2- eingeschraubt in Oberöffnung des Kollektors
Zubehör:	Extra bestellen	

