

Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B	A							
QB00595078502G030000	595	785	101-106	50	53-58	525	0,74	11,0	3,5	374	337	198	300
QB00595118502G030000	595	1185	101-106	50	53-58	525	1,15	16,3	5,3	586	528	310	300
QB00595169802G030000	595	1698	101-106	50	53-58	525	1,70	23,2	7,8	849	765	448	600

Horizontal profiles:		Vertical manifolds:	
Finishing and warranty:	Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;		
Mounting brackets:	brackets in the colour of the radiator are included		
Valve:	- integrated, hidden under cover; - thermostatic valve included		
Heater :	order separately		
Working pressure:	4 bars		
Maximum temperature:	95°C		
Connections:		- inner threads G 1/2 - air-vent plug G1/8 hidden behind	
Remarks:	- water inlet on the left side - chrome-plated thermostatic head		
Accessories:	order separately		

