



Kod produktu	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B								
RMM0595094414A030000	595	944	72-77	50	52-57	525	1,00	17,3	5,3	470	423	245	300
RMM0595144814A030000	595	1448	72-77	50	52-57	525	1,47	25,7	7,5	693	623	362	600

Horizontal tubes: 

Circuital profile: 

Finishing and warranty: Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;

Mounting brackets: brackets in the same colour as the radiator are included

Mirror: Mirror can be with phase or without. Size of mirror for RMM-609: 452x802 mm and for RMM-614: 450x1306 mm.


Valve: order separately

Heater: order separately

Accessories: order separately

Working pressure: 4 bars

Maximum temperature: 120 °C

Connections:  For the position of connections consult technical drawings on this page
 – inner threads G 1/2
 – pipe span: 50 mm

