



Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m <sup>2</sup> ]	Weight [kg]	Capacity [dm <sup>3</sup> ]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B	A							
RV0045008950230E0000	450	895	90-95	410	75-80	410	0,57	6,7	2,6	315	284	167	300
RV0045013250230E0000	450	1325	90-95	410	75-80	410	0,75	8,9	3,7	415	374	220	300
RV0045015050230E0000	450	1505	90-95	410	75-80	410	0,84	9,9	4,1	465	419	246	300
RV0045016950230E0000	450	1695	90-95	410	75-80	410	0,93	10,9	4,6	514	464	273	300
RV0055508950230E0000	555	895	90-95	515	75-80	515	0,66	7,8	2,9	365	329	194	300
RV0055513250230E0000	555	1325	90-95	515	75-80	515	0,87	10,2	4,0	481	434	255	300
RV0055515050230E0000	555	1505	90-95	515	75-80	515	0,96	11,2	4,5	531	479	282	300
RV0055516950230E0000	555	1695	90-95	515	75-80	515	1,06	12,4	5,0	586	529	311	300

Horizontal profiles:



Vertical manifolds:



Finishing and warranty: Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;

Mounting brackets: brackets in the colour of the radiator are included

Valve: order separately

Heater : order separately

Working pressure: 8 bars

Maximum temperature: 120 °C

Connections:



- inner threads G 1/2  
- air-vent plug G1/8 hidden behind

Accessories: order separately

Remarks:

