




| Type                 | Width [mm] | Height [mm] | Depth from wall [mm] | Connections spacing [mm] | Connections distance from the wall [mm] | Brackets spacing [mm] | Heating surface [m <sup>2</sup> ] | Weight [kg] | Capacity [dm <sup>3</sup> ] | Power ΔT=50K (75/65/20 °C) [W] | Power ΔT=46K (75/65/24 °C) [W] | Power ΔT=30K (55/45/20 °C) [W] | Electric heater maximum power [W] |
|----------------------|------------|-------------|----------------------|--------------------------|---|-----------------------|-----------------------------------|-------------|-----------------------------|--------------------------------|--------------------------------|--------------------------------|-----------------------------------|
|                      | W          | H           | D                    | C                        | B                                       | A                     |                                   |             |                             |                                |                                |                                |                                   |
| SRP0600060014L071000 | 600        | 600         | 138                  | 50                       | 113                                     | 490                   | 2,18                              | 35,2        | 14,4                        | 690                            | 621                            | 362                            | -                                 |
| SRP0600048614L071000 | 600        | 486         | 138                  | 50                       | 113                                     | 490                   | 1,77                              | 30,2        | 12,0                        | 572                            | 515                            | 300                            | -                                 |
| SRP1000060014L071000 | 1000       | 600         | 138                  | 50                       | 113                                     | 890                   | 3,05                              | 50,4        | 22,0                        | 1096                           | 987                            | 575                            | -                                 |
| SRP1000048614L071000 | 1000       | 486         | 138                  | 50                       | 113                                     | 890                   | 2,48                              | 42,6        | 18,2                        | 913                            | 822                            | 480                            | -                                 |
| SRP1400060014L071000 | 1400       | 600         | 138                  | 50                       | 113                                     | 1290                  | 3,92                              | 65,5        | 29,6                        | 1508                           | 1357                           | 791                            | -                                 |
| SRP1400048614L071000 | 1400       | 486         | 138                  | 50                       | 113                                     | 1290                  | 3,18                              | 55,0        | 24,4                        | 1254                           | 1129                           | 658                            | -                                 |
| SRP1800060014L071000 | 1800       | 600         | 138                  | 50                       | 113                                     | 1690                  | 4,79                              | 80,6        | 37,2                        | 1920                           | 1728                           | 1008                           | -                                 |
| SRP1800048614L071000 | 1800       | 486         | 138                  | 50                       | 113                                     | 1690                  | 3,89                              | 67,4        | 30,7                        | 1595                           | 1436                           | 837                            | -                                 |
| SRP2200060014L071000 | 2200       | 600         | 138                  | 50                       | 113                                     | 2090                  | 5,66                              | 95,8        | 44,9                        | 2333                           | 2100                           | 1225                           | -                                 |
| SRP2200048614L071000 | 2200       | 486         | 138                  | 50                       | 113                                     | 2090                  | 4,60                              | 79,8        | 36,9                        | 1937                           | 1744                           | 1017                           | -                                 |



Vertical manifolds (atypical);  
2 mm thick tube

|                         |   |
|-------------------------|---|
| Finishing and warranty: | Cataphoresis + polyester-epoxy lacquer;<br>5 year warranty;   |
| Mounting brackets:      | Galvanized snap fastener mounting brackets are included   |
| Valve:                  | order separately  |
| Heater:                 | -   |
| Working pressure:       | 8 bars  |
| Maximal temperature:    | 120 °C  |
| Connections:            | <br>inner threads G 1/2<br>air-vent plug G1/8 hidden behind  |
| Remarks:                | <ul style="list-style-type: none"> <li>- Location of connections and the feed pipe: on the left side of the radiator</li> <li>- Connections to the right side available upon request (in this case the feed pipe is on the right side, whereas the return pipe is on the left)</li> </ul> |

