



Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m <sup>2</sup> ]	Weight [kg]	Capacity [dm <sup>3</sup> ]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B								
TS0045008710240D0000	450	871	60-65	420	45-50	420	0,52	9,8	4,6	321	290	171	-
TS0045011950240D0000	450	1195	60-65	420	45-50	420	0,70	13,1	6,2	434	392	231	300
TS0045015190240D0000	450	1519	60-65	420	45-50	420	0,89	16,3	7,9	483	436	258	300
TS0060011950240D0000	600	1195	60-65	570	45-50	570	0,88	16,3	6,7	537	484	286	300
TS0060015190240D0000	600	1519	60-65	570	45-50	570	1,11	20,4	8,5	675	609	360	300

Horizontal profiles:



Vertical manifolds:



Finishing and warranty:

Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;

Mounting brackets:

brackets in the colour of the radiator are included

Valve:

order separately

Heater :

order separately

Working pressure:

8 bars

Maximum temperature:

120 °C

Connections:



- inner threads G 1/2
- air-vent plug G 1/2 screwed in the upper hole of the collector, included

