



Kod produktu	Breite [mm]	Höhe [mm]	Tiefe [mm]	Anschlussabstand [mm]	Abstand der Verschraubung von der Wand [mm]	Halteabstand [mm]	Heizfläche [m ²]	Gewicht [kg]	Wasserinhalt [dm ³]	Leistung ΔT=50K (75/65/20 °C) [W]	Leistung ΔT=46K (75/65/24 °C) [W]	Leistung ΔT=30K (55/45/20 °C) [W]	Max. Leistung vom Elektro-Heizstab [W]
	W	H	D	C	B	A							
TG00606081802B030000	606	818	66-71	50	52-57	520	0,77	8,7	4,3	419	379	226	300
TG00606123802B030000	606	1238	66-71	50	52-57	520	1,20	13,2	6,8	656	592	353	600
TG00606174202B030000	606	1742	66-71	50	52-57	520	1,73	18,7	9,7	943	851	504	900

Waagerechte Rohren



Vertikale Sammelrohren



Fertigstellung und Garantie:

Nanokeramik (Zirkoniumoxid-Beschichtung) + Polyester-Epoxydlack; Garantie 5 Jahre

Befestigungen

Befestigungsset; Befestigungsset in Heizkörperfarbe

Ventil:

Extra bestellen

Heizstab:

Extra bestellen

Zubehör:

Extra bestellen

Arbeitsdruck:

6 Bar

Max Temperatur:

120 °C

Anschlüsse:



Innengewinde G1/2
Entlüfter G 1/8 versteckt von hinten

TG

