


Available colors: RAL palette, ENIX palette


Heater colors: white, black matt, silver, chrome

Index*	Width [mm]	Width including heater [mm]	Height [mm]	Width including heater [mm]	Depth [mm]	Brackets spacing [mm]	Weight [kg]	Power [W]
	W	W1	H	H1	D	A		
EBL0430083001E2N0000	430	453	830	925	65-70	400	9,5	300
EBL0430103001E2N0000	430	453	1030	1125	65-70	400	11,3	300
EBL0430123001E2N0000	430	453	1230	1325	65-70	400	13,0	300
EBL0430153001E2N0000	430	453	1530	1625	65-70	400	15,7	300
EBL0530083001E2N0000	530	553	830	925	65-70	500	10,8	300
EBL0530103001E2N0000	530	553	1030	1125	65-70	500	12,7	300
EBL0530123001E2N0000	530	553	1230	1325	65-70	500	14,7	300
EBL0530153001E2N0000	530	553	1530	1625	65-70	500	17,7	300
EBL0630083001E2N0000	630	653	830	925	65-70	600	12,0	300
EBL0630103001E2N0000	630	653	1030	1125	65-70	600	14,2	300
EBL0630123001E2N0000	630	653	1230	1325	65-70	600	16,4	300
EBL0630153001E3N0000	630	653	1530	1625	65-70	600	19,7	600

*Index for the white towel warmer with a heating element on the right side.



Billo EBL 530x830 left configuration axonometric drawing



Billo EBL 530x830 right configuration axonometric drawing

Horizontal profiles		Vertical manifolds	
Finish and warranty:	Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 2-year warranty		
Mounting brackets:	Wall mounting set included; brackets matching the color of the radiator.		
Heating element:	GV		
Maximum temperature:	75°C		
Working environment:	antifreeze fluid		
Input:	230V; 50Hz		
Protection class:	I class		
Enclosure protection class:	IP54		
Heater connection:	<div style="display: flex; align-items: center; gap: 20px;"> <div style="border: 1px solid black; padding: 2px;">EBL left</div> <div style="font-size: 20px;">or</div> <div style="border: 1px solid black; padding: 2px;">EBL right</div> </div> <div style="display: flex; align-items: center; gap: 20px;"> <div style="text-align: center;">GV </div> <div style="text-align: center;"> GV</div> </div>		

