

| Kod produktu* | Szerokość [mm] | Wysokość [mm] | Głębokość [mm] | Rozstaw przyłączy [mm] | Długość przyłączy od ściany [mm] | Rozstaw uchwytów [mm] | Powierzchnia grzewcza [m ²] | Masa [kg] | Pojemność [dm ³] | n | K _m | Moc dla ΔT=50K (75/65/20 °C) [W] | Moc dla ΔT=46K (75/65/24 °C) [W] | Moc dla ΔT=30K (55/45/20 °C) [W] | Maksymalna moc grzałki elektrycznej [W] |
|---------------------|----------------|---------------|----------------|------------------------|----------------------------------|-----------------------|-----------------------------------------|-----------|------------------------------|--------|----------------|----------------------------------|----------------------------------|----------------------------------|-----------------------------------------|
| | W | H | D | C | B | A | | | | | | | | | |
| HB0043007500240N000 | 430 | 750 | 65-70 | 400 | 50-55 | 400 | 0,50 | 5,3 | 2,0 | 1,2556 | 2,0382 | 277 | 249 | 146 | - |
| HB0043009500240N000 | 430 | 950 | 65-70 | 400 | 50-55 | 400 | 0,63 | 6,6 | 2,6 | 1,2556 | 2,5386 | 345 | 311 | 182 | 300 |
| HB0043011500240N000 | 430 | 1150 | 65-70 | 400 | 50-55 | 400 | 0,76 | 7,9 | 3,1 | 1,2556 | 3,0316 | 412 | 371 | 217 | 300 |
| HB0043014500240N000 | 430 | 1450 | 65-70 | 400 | 50-55 | 400 | 1,02 | 10,5 | 4,1 | 1,2556 | 4,0765 | 554 | 499 | 292 | 300 |
| HB0053007500240N000 | 530 | 750 | 65-70 | 500 | 50-55 | 500 | 0,59 | 6,1 | 2,3 | 1,2556 | 2,4135 | 328 | 295 | 173 | 300 |
| HB0053009500240N000 | 530 | 950 | 65-70 | 500 | 50-55 | 500 | 0,75 | 7,6 | 2,9 | 1,2556 | 2,9948 | 407 | 367 | 214 | 300 |
| HB0053011500240N000 | 530 | 1150 | 65-70 | 500 | 50-55 | 500 | 0,90 | 9,1 | 3,5 | 1,2556 | 3,6230 | 492 | 443 | 259 | 300 |
| HB0053014500240N000 | 530 | 1450 | 65-70 | 500 | 50-55 | 500 | 1,21 | 12,2 | 4,6 | 1,2556 | 4,8638 | 661 | 595 | 348 | 600 |
| HB0063007500240N000 | 630 | 750 | 65-70 | 600 | 50-55 | 600 | 0,68 | 6,9 | 2,5 | 1,2556 | 2,7888 | 379 | 341 | 200 | 300 |
| HB0063009500240N000 | 630 | 950 | 65-70 | 600 | 50-55 | 600 | 0,86 | 8,6 | 3,2 | 1,2556 | 3,4952 | 475 | 428 | 250 | 300 |
| HB0063011500240N000 | 630 | 1150 | 65-70 | 600 | 50-55 | 600 | 1,03 | 10,3 | 3,9 | 1,2556 | 4,1574 | 565 | 509 | 298 | 300 |
| HB0063014500240N000 | 630 | 1450 | 65-70 | 600 | 50-55 | 600 | 1,40 | 13,9 | 5,1 | 1,2556 | 5,6511 | 768 | 692 | 404 | 600 |

*Kod dla grzejnika w kolorze białym RAL 9016 mat.

