

Hyacinth H, HX

(Hiacynt H, HX)

Kod produktu*	Szerokość [mm]	Wysokość [mm]	Głębokość [mm]	Rozstaw przyłączy [mm]	Długość przyłączy od ściany [mm]	Rozstaw uchwytyłów [mm]	Powierzchnia grzewcza [m ²]	Masa [kg]	Pojemność [dm ³]	n	K _m	Moc dla ΔT=50K (75/65/20 °C) [W]	Moc dla ΔT=46K (75/65/24 °C) [W]	Moc dla ΔT=30K (55/45/20 °C) [W]	Maksymalna moc grzałki elektrycznej [W]
	W	H	D	C	B	A									
H00040007730230D0000	400	773	65-70	360	45-50	360	0,52	6,2	2,4	1,2151	2,1726	252	228	135	150
H000400077302G0E0000	400	773	90-95	50	54-59	360	0,52	6,2	2,4	1,2151	2,1726	252	228	135	150
H00040010430230D0000	400	1043	65-70	360	45-50	360	0,75	8,8	3,3	1,2406	2,6452	339	306	180	300
H000400104302G0E0000	400	1043	90-95	50	54-59	360	0,75	8,8	3,3	1,2406	2,6452	339	306	180	300
H00040013130230D0000	400	1313	65-70	360	45-50	360	0,97	11,4	4,3	1,2546	3,2577	441	397	232	300
H000400131302G0E0000	400	1313	90-95	50	54-59	360	0,97	11,4	4,3	1,2546	3,2577	441	397	232	300
H00040015830230D0000	400	1583	65-70	360	45-50	360	1,17	13,7	5,1	1,2624	3,7903	529	476	278	300
H000400158302G0E0000	400	1583	90-95	50	54-59	360	1,17	13,7	5,1	1,2624	3,7903	529	476	278	300
H00055507730230D0000	555	773	65-70	515	45-50	515	0,67	8,0	2,8	1,2151	2,7934	324	293	174	300
H000555077302G0E0000	555	773	90-95	50	54-59	515	0,67	8,0	2,8	1,2151	2,7934	324	293	174	300
H00055510430230D0000	555	1043	65-70	515	45-50	515	0,97	11,5	3,9	1,2406	3,4333	440	397	233	300
H000555104302G0E0000	555	1043	90-95	50	54-59	515	0,97	11,5	3,9	1,2406	3,4333	440	397	233	300
H00055513130230D0000	555	1313	65-70	515	45-50	515	1,27	14,8	5,1	1,2546	4,2476	575	518	303	300
H000555131302G0E0000	555	1313	90-95	50	54-59	515	1,27	14,8	5,1	1,2546	4,2476	575	518	303	300
H00055515830230D0000	555	1583	65-70	515	45-50	515	1,53	17,8	6,1	1,2624	4,9439	690	621	362	600
H000555158302G0E0000	555	1583	90-95	50	54-59	515	1,53	17,8	6,1	1,2624	4,9439	690	621	362	600

*Kod dla grzejnika w kolorze białym RAL 9016 połysk.

