


Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m <sup>2</sup> ]	Weight [kg]	Capacity [dm <sup>3</sup> ]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B	A							
AR005000817014010000	500	817	97-102	424	51-56	435	0,7	7,6	3,9	386	349	210	300
AR00500081701C010000	500	817	97-102	50	86-91	435	0,7	7,6	3,9	386	349	210	300
AR005001237014010000	500	1237	97-102	424	51-56	435	1,1	11,6	6,1	600	543	324	600
AR00500123701C010000	500	1237	97-102	50	86-91	435	1,1	11,6	6,1	600	543	324	600
AR005001741014010000	500	1741	97-102	424	51-56	435	1,5	16,2	8,5	844	762	451	600
AR00500174101C010000	500	1741	97-102	50	86-91	435	1,5	16,2	8,5	844	762	451	600
AR006000817014010000	600	817	105-110	524	51-56	535	0,8	8,5	4,2	450	407	245	300
AR00600081701C010000	600	817	105-110	50	94-99	535	0,8	8,5	4,2	450	407	245	300
AR006001237014010000	600	1237	105-110	524	51-56	535	1,3	13,0	6,9	701	634	378	600
AR00600123701C010000	600	1237	105-110	50	94-99	535	1,3	13,0	6,9	701	634	378	600
AR006001741014010000	600	1741	105-110	524	51-56	535	1,8	18,3	9,7	987	892	528	900
AR00600174101C010000	600	1741	105-110	50	94-99	535	1,8	18,3	9,7	987	892	528	900
AR007500817014010000	750	817	119-124	675	51-56	685	1,0	9,9	5,2	546	494	296	300
AR00750081701C010000	750	817	119-124	50	108-113	685	1,0	9,9	5,2	546	494	296	300
AR007501237014010000	750	1237	119-124	675	51-56	685	1,6	15,2	8,2	856	773	461	600
AR00750123701C010000	750	1237	119-124	50	108-113	685	1,6	15,2	8,2	856	773	461	600
AR007501741014010000	750	1741	119-124	675	51-56	685	2,2	21,3	11,5	1203	1086	644	900
AR00750174101C010000	750	1741	119-124	50	108-113	685	2,2	21,3	11,5	1203	1086	644	900



Finishing and warranty: Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;

Mounting brackets: brackets in the colour of the radiator are included


Valve: order separately

Heater : order separately

Accessories: order separately

Working pressure: 8 bars

Maximum temperature: 120°C

Connections:  - inner threads G 1/2  
- air-vent plug G 1/2, screwed in the upper hole of the collector is included

